


Description	Value
<b>General information:</b>	
Product name:	NBG 125-100-160/176 BAFE2CESBQQEKW3
Product No:	On request
EAN number:	On request
<b>Technical:</b>	
Pump speed on which pump data are based:	1445 rpm
Rated flow:	120.2 m <sup>3</sup> /h
Rated head:	7.051 m
Actual impeller diameter:	176 mm
Nominal impeller diameter:	160
Shaft seal arrangement:	Single
Shaft diameter:	32 mm
Code for shaft seal:	BQQE
Curve tolerance:	ISO9906:2012 3B2
Pump version:	AF
Bearing design:	Standard
<b>Materials:</b>	
Pump housing:	Cast iron
Pump housing:	EN-GJL-250
Pump housing:	ASTM class 35
Wear ring:	Bronze
Impeller:	Cast iron
Impeller:	EN-GJL-200
Impeller:	ASTM class 30
Internal pump house coating:	CED
Material code:	C
Code for rubber:	E
Shaft:	Stainless steel
Shaft:	EN 1.4401
Shaft:	AISI 316
<b>Installation:</b>	
t max amb:	40 °C
Maximum operating pressure:	16 bar
Pipe connection standard:	AS2129 table E
Size of inlet connection:	DN 125
Size of outlet connection:	DN 100
Pressure rating for connection:	PN 16
Bearing lubrication:	Grease
Pump housing with feet:	Yes
Support block (Yes/No):	N
Connect code:	E2
<b>Liquid:</b>	
Pumped liquid:	Water
Liquid temperature range:	-25 .. 120 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m <sup>3</sup>
<b>Electrical data:</b>	
Motor type:	WEG
IE Efficiency class:	IE3
Rated power - P2:	4 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-660/415-690 V
Rated current:	8,47-4,88/8,09-4,75 A
Cos phi - power factor:	0.81
Rated speed:	1445 rpm
Efficiency:	IE3 88,6%
Motor efficiency at full load:	88.6-89.3 %
Motor efficiency at 3/4 load:	89-88.9 %





**Company name:** NTD Pumps And Mechanical Construction Co.,LTD  
**Created by:** Tien Nguyen Van  
**Phone:** 0949570529  
**Email:** tien.nv@ntdpumps.com  
**Date:** 21/05/2022

Description	Value
Number of poles:	4
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Built-in motor protection:	NONE
Motor No:	99737195
Mount. design. acc. IEC 34-7:	IM B5
<b>Controls:</b>	
Frequency converter:	NONE
Pressure sensor:	N
<b>Others:</b>	
Minimum efficiency index, MEI $\geq$ :	0.70
Net weight:	112 kg
Gross weight:	128 kg
Shipping volume:	0.315 m <sup>3</sup>